General
Tower Attachments
 Hardwares
Suspension Clamps and Armour Rod
 Tension Clamps
Earth wire Clamps and Grounding Systems
Arcing Devices
Spacers & Spacer Dampers
Stock Bridge Dampers
Accessories
OPGW Fittings

# **Tower Attachments**

# **TABLE OF CONTENTS**

PAGE

**U-Bolts** 










Website: www.yap-co.com




# Tower attachments





Catalogue.No	Br. Load (kN)	D1	D2	D3
C0910802	120	94	18	22
C0910803	210	94	22	22






Hc	ıγ	ι			r	
24.0					٠.	

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
C1010701	120	75	20	24	20
C10I1201	420	100	30	42	32
C10I1205	500	100	33	42	32





U Bolt

Catalogue.No	Br. Load (kN)	D1	D2	D3
U1661400	120	140	70	16
U1861530	160	153	70	18
U2061550	210	155	70	20
U2061800	210	180	70	20
U2241800	210	180	90	22



### Notes:

All dimensions are in mm.
All noted dimensions are upon Request.

Website: www.yap-co.com

E-mail: info@yap-co.com



# **Hardwares**

TABLE OF CONTENTS	PAGE
Oval Balls and Ball Eyes	3/2 - 3/3
Ball Clevises	3/4
Socket Eyes	3/5 - 3/6
Socket Clevises	3/7 - 3/8
Shackles	3/9 - 3/10
Extension Links	3/11
Adjustable Extension Links	3/12
Turn Buckles	3/13
Yoke Plates	3/14- 3/15
Clevis Connectors & Clamp Connectors & Y-Clevis Eyes	3/16- 3/17
Sag Adjasters and Chains	3/18




Website: www.yap-co.com


E-mail: info@yap-co.com




# Oval Balls



Catalogue.No	Br. Load (kN)	<b>D</b> 1	D2	D3	D4
B16OA06		100		25	18



Catalogue.No Br. Load (kN)	<b>D</b> 1		D3	D4
<b>B16OA011</b> 120	127	46	25	18
<b>B20OA02</b> 160	146	45	34	21



	*******						
Catalogue.No	Br. Load (kN)	D1 D2	D3	D4			
B16OA01	120	131 48	25	16			



All dimensions are in mm.

Website: www.yap-co.com











# Ball Eyes



Twisted Ball Eye

Catalogue.No	Br. Load (kN)	<b>D</b> 1	D2	D3	D4
B16OA08	120	107	52		24





Ball Eye

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
B20EA02	210	146			22




Note:

All dimensions are in mm.

Website: www.yap-co.com




# Ball Clevises



Ball Clevis

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
B16UO01	120	68	34	18	16
B20UO04	160	85	44	22	18
B16UO03	210	85	44	22	20






Y\_Ball Clevis

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
B16YO03	80	85			16
B16YO04	120	94			18
B20YO01	160	101			20
B20YO02	210	101			22





Y\_Ball Clevis

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
B16YO05	120	134	48		18
B20YO03	160	148	53		20
B20YO04	210	148	53		22



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# Sockets Eyes




D2



C	atalogue.No	Br. Load (kN)	D1	D2	D3	D4	Mat.
	OSW16A06	120	106	19	17.5	55	Ductile Iron






Socket Eye

Catalogue.No	Br. Load D1 D2	D3 D4 Mat.
OSW16A07	120 106 19	17.5 55 F. St.






Socket Eye

	Catalogue.No	Br. Load D1	D2 D3 D4	Mat.
3	OSW16A05		19 17.5 52	Ductile Iron





Socket Eye

Br. Load (kN)	D1	D2	D3	D4	Mat.
120	114	35	17.5	53	Ductile Iron
120	112	50	17.5	52	F. St.
120	112	50	17.5	52	Ductile Iron
	(kN) 120	(kN) D1 120 114	(kN) D1 D2  120 114 35	Br. Load (kN)         D1         D2         D3           120         114         35         17.5           120         112         50         17.5	(kN)         D1         D2         D3         D4           120         114         35         17.5         53           120         112         50         17.5         52



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com




# Socket Eye



Socket Eye

Catalogue.No	(kN)	D1	D2	D3	D4	Mat.
OSN16A02		92	100	24		Iron





Twisted Socket Eye

Catalogue.No	Br. Load (kN)	D1	D2	D3 D4	Mat.
OSW16A0D	120	128	55	19 24	Ductile
				13,132	11011




Note:

All dimensions are in mm.

Website: www.yap-co.com




# Socket Clevises



Y\_Socket Clevis

Catalogue.No	Br. Load (kN)	D1	<b>D2</b>	D3	D4	Mat.
ODS16O07	120	75			18	F.St.
ODS20O07	160	82			20	F.St.
ODS20O09	210	91			22	F.St.





Y\_Socket Clevis

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	Mat.
ODS16O05	120	75			18	Ductile Iron



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com




# Socket Clevises



### Socket Clevis

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	Mat.
ODS16O06	120	71	38	21	16	F.St.
ODS20O05	160	96	55	22	18	F.St.
ODS20O03	210	96	55	21	20	F.St.






### Socket Clevis

Catalogue.No	Br. Load D1	D2	D3	D4	Mat.
ODS16001	120 71	38	10	10	Ductile Iron





### Socket Clevis

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	Mat.
ODL16A01	120	123	40	20	16	56	Ductile Iron
ODL20A02	160	151	55	24	18	63	F.St.
ODL20A03	210	151	55	24	20	63	F.St.



### Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com




# Shackles




Catalogue.No	Br. Load (kN)	D1	D2	D3
H08B1000	80	100	24	16
H12B0800	120	80	26	16
H16B0800	160	80	26	18
H21B0900	210	90	26	20
H24B0900	240	90	26	22
H32B1000	320	100	28	27
H42B1150	420	115	36	30
H52B1150	520	115	36	33





Catalogue.No Br. Load (kN)	D1	D2	D3
H42B1000 420	100	30	30
<b>H48B1300</b> 520	130	24	33





Catalogue.No	Br. Load (kN)	D1	D2
H08V0950	80	95	16
H12V0950	120	95	18



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com




# Shackles



Catalogue.No	Br. Load (kN)	D1	D2	D3
H12B0760	120	76	24	16
H12B1220	120	122	26	16





Catalogue.No	Br. Load (kN)	D1 D2 D	3
H07D1100	70	110 70 16	,
H08D1301	80	130 85 16	ó
H08D1302	80	130 75 16	ó



### Notes:


All dimensions are in mm.
All noted dimensions are upon Request.

Website: www.yap-co.com

E-mail: info@yap-co.com




# **Extension Links**




### Simple Link

(	Catalogue.No	Br. Load (kN)	D1	D2
	LE012001	210	120	16



### Forge Link


ogue.No Br. Load	D1	D2
<b>50701</b> 210	457	22




### Clevis Link


Catalogue.No Br. Load (kN)	D1 D2	D3
LE030010 120	300 22	16







Double .	Boaste Striepts Buttle					
Catalogue.No	Br. Load (kN)	D1	D2			
LE01000A	420	100	30			




All dimensions are in mm.

All noted dimensions are upon Request.

Website: www.yap-co.com




# Adjustable Extension Links



### Tongue-Tongue

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5
LA405801	420	400-580	20	30	125	20






### Clevis-Clevis

Catalogue.No	Br. Load (kN)	D1 D2	D3	D4	D5
LA375702	320	370-570 30	30	27	200





### ${\it Clevis-Tongue}$

	_					
Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5
LA649901	210	638-990	24	20	16	355







All dimensions are in mm.
All noted dimensions are upon Request.

Website: www.yap-co.com




# Turn Buckles





Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
LT45220A	120	450-600	22	35	16
LT45220D	160	450-600	22	35	18
LT552750	210	550-850	24	40	20



Catalogue.No	Br. Load (kN)		D2	D3	D4	D5
LT45220C	160	450-600	35	22	20	20
LT552703	160	550-850		24	20	20




All dimensions are in mm.


Website: www.yap-co.com







# Yoke Plates







	D1	D2	D3
Y5118L04 500	457	90	18



	111111					
Catalogue.No	Br. Load (kN)	D1 D2	D3			
Y2P16N04	240	457 170	16			





All dimensions are in mm.


All noted dimensions are upon Request.

Website: www.yap-co.com

E-mail: info@yap-co.com




# Yoke Plates




Catalogue.No	Br. Load (kN)	D1	D2	D3
Y1R16N02	120	457	70	16
Y2R16N03	240	457	70	16






Catalogue.No	Br. Load		D2	D3
Y1T16L0A	120	457	70	16
	320	43/	90	18
Y4T18L04	420	457	140	18






Catalogue	.No Br. Loau	D1 D2	D3
	(KIV)		
V/2D101 OF	220	457 150	10
T SP 18LUL	)	43/ 130	18
Y3P18L0C	420	457 150	18








Website: www.yap-co.com

All noted dimensions are upon Request.

E-mail: info@yap-co.com




# Clevis Connectors



Catalogue.No	Br. Load (kN)	<b>D</b> 1	D2	D3	D4	D5
C07U5002	120	70	18	20	16	16
C07U5006		70	18	20	18	18
C08U5001	210	80	24	26	20	20





Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5
C08U5005	160	80	24	17	18	18
C08U5003	210	80	24	16	20	20
C11U7005	320	110	28	22	27	22
C15U8001	420	150	22	22	30	30
C15U8002	480	150	22	22	33	33



### Notes:

All dimensions are in mm.


All noted dimensions are upon Request.

Website: www.yap-co.com

E-mail: info@yap-co.com




# Connectors



### Clamp Connector

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
C08U3001	80	80	20	30	16
C08U3701	120	80	22	37	16
C08U4501	120	80	22	45	16
C08U5201	120	80	22	52	16
C08U5801	120	80	22	56	16





### Y-Clevis Eye

Catalogue.No	Br. Load (kN)	D1	D2	D3	D4
C09Y4602	120	90	46	22	18
C09Y4601	160	90	46	22	20



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# Links




Sag adjuster

All Noted dimensions are upon Request.

Catalogue.No	Br. Load (kN)	D1	D2	D3	
LS081803	120	180	80	18	
LS162003	160	200	164	20	
LS385701	210	570	380	22	






### Sag adjuster

All Noted dimensions are upon Request.


Catalogue, No Br. Load (kN)	D1	D2	D3	D4
LS204003 160	200-405	18		20





### Chain

Catalogue.No	Br. Load (kN)	D1	D2	D3
LC902221	240	90	22	32
LC122521	320	120	25	51
LC122821	480	120	28	51



Note:

All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# **Suspension Clamps and Armour Rod**

# TABLE OF CONTENTS

**PAGE** 

Suspension Clamp for Conductors

4/2

Suspension Clamp for Shield wires

4/2 - 4/3

Armour Rod for Conductors

4/4


Armour Rod for Shield wires

4/5

Website: www.yap-co.com




# Suspension Clamps




Catalogue.No	Br. Load (kN)	<b>D</b> 1	D2	D3	D4	D5	Mat.
SCOSSS03	120	265	48	24-27	16	43	AL
SCASSS01	120	285	56	36-38	16	49	AL
SCACCS02	120	285	56	41-45	16	56	AL
SCACUS01	120	285	59	50	16	63	AL





Catalogue.No		D1	D2	D3	D4	D5	Mat.
	120		58	24-32	16	42	AL





Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	Mat.
SCOSHS02	70	230	103	12-20	16	20	AL
SCASLS0	80	200	100	19-30	16	20	AL



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# Suspension Clamps



Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	Mat.
SSAH78S0	80	150	93.5	8-17	16	63	Ductile Iron
SSAH7S01	70	150	93.5	8-17	16	63	AL
SSOHLS0	80	130	97	9-13	16	50	Ductile Iron
SSAH7601	80	178	98.5	9-20	16	73	Ductile Iron
SCASLS02	80	200	130	19-30	16	78	AL
SSAH7S01	80	198	106	20-27	16	66	AL



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# Armour Rods For Conductor



Wire	Number	No. of Rods	D1	D2	Mat.
Aster 148	ACA1246L	12	1626	4.62	AL
Aster 366	ACA1179L	13	2340	7.9	AL
400/50	ACC1208L	12	2440	7.9	AL
Hyena	ACY1105L	11	1520	4.6	AL
Wolf	ACW1305L	13	1830	5.2	AL
Lynx	ACL1305L	13	1830	5.2	AL
Hen	AC11206L	12	1980	6.4	AL
Hawk	ACH1206L	12	1980	6.4	AL
Squab	ACS1306L	13	2240	6.4	AL
Condor	ACN1208L	12	2440	7.9	AL
Drake	ACD1208L	12	2540	7.9	AL
Canary	ACC1308L	13	2540	7.9	AL
Rail	ACR1308L	13	2540	7.9	AL
Cardinal	ACF1306L	13	2540	7.9	AL
Curlew	ACU1209L	12	2540	9.3	AL
Martin	ACM1309L	13	2540	9.3	AL



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# Armour Rods For Shield Wire





Wire	Number	No. of Rods	D1	D2	Mat.
7 # 10	AS710903	9	1168	2.9	AL
Core of Wolf	ASW1028S	10	864	2.79	St.
Core of Hawk	ASH1128S	11	864	2.79	St.
Core of Hawk	ASH0803L	8	1118	3.66	AL
3#6	AS361103		890	2.79	St.
Core of Lynx	ASL1128L	11	890	2.79	St.
7 # 8	AS71132L	11	940	3.28	St.
7 # 8 AW	AS71003S	10	915	3.7	AL
Core of Canary	ASC1132L	11	940	3.28	St.
Core of Curlew	ASU1232S	12	990	3.28	St.
Core of Curlew	ASU1004L	10	1320	4	AL
Core of Martin	ASM1232S	12	1070	3.28	St.
7 # 6	AS71004L	10	1370	4.2	AL



Note:

All dimensions are in mm.

Website: www.yap-co.com



# **Tension Clamps**

# TABLE OF CONTENTS

**PAGE** 

Campression Dead End Clamps for ACSR conductors

5/2

Campression Dead End Clamps for AAC & AAAC conductor

5-3 - 5/4

;; E/E

for shield wires

Campression Dead End Clamps

5/5

**Bolted type Tension Clamps** 

5/6







Website: www.yap-co.com



# Tension Clamps for Conductor(Compression Type)



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	D6	D7	D8
Squab	TCXQSH31	95% UTS Cond.	26.5	40	26	75	9.4	18	18	520
400 mm <sup>2</sup>	TCX26S31	50% UTS Cond.	27.4	40	26	75			18	520
Drake	TCXDSH32	95% UTS Cond.	30	50	26	75	11.5	22	18	620
<b>500 mm<sup>2</sup></b>	ТСХ31Н31	50% UTS Cond.	32	52	26	75			18	650
Canary	TCXCSH36	95% UTS Cond.	32	52	26	75	11	18	18	650
curlew	TCXUSH39	95% UTS Cond.	34	52	26	75	12.5	18	18	650
<b>625</b> mm <sup>2</sup>	ТСХ33Н39	50% UTS Cond.	34	52	26	75			18	620



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	D6	<b>D7</b>	D8
Hyena	TCXYSH34	95% UTS Cond.	15.5	25	22	55	6.5	12	16	330
Lynx	TCXLSH34	95% UTS Cond.	21	32	22	55	8.7	17	16	420
Hawk	тсхнѕнз6	95% UTS Cond.	23	36	22	55	8.4	18	16	480

Note:


All dimensions are in mm.

Website: www.yap-co.com


E-mail: info@yap-co.com



# Compression Dead end clamps for AAC & AAAC conductors



Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	<b>D</b> 5	D6	D7	D8
TCXLSH35	95% UTS Cond.	21	32	22	55	8.7	17	420	16
тсхнѕнз8	95% UTS Cond.	23	36	22	55	8.4	18	480	16
TCXQSH32	95% UTS Cond.	26.5	40	26	75	9.4	18	520	18
TCX26S32	50% UTS Cond.	27.4	40	26	7.5			520	18
ТСХ31Н32	50% UTS Cond.	32	52	26	75		—	650	18
TCXCSH37	95% UTS Cond.	32	52	26	75	11	22	650	18
TCXUSH32	95% UTS Cond.	34	52	26	75	12.5	24	650	18
ТСХ33Н37	50% UTS Cond.	34	52	24	75			650	18
	TCXLSH35 TCXHSH38 TCXQSH32 TCX26S32 TCX31H32 TCXCSH37 TCXUSH32	TCXLSH35 95% UTS Cond.  TCXHSH38 95% UTS Cond.  TCXQSH32 95% UTS Cond.  TCX26S32 50% UTS Cond.  TCX31H32 50% UTS Cond.  TCXCSH37 95% UTS Cond.  TCXUSH32 95% UTS Cond.	TCXLSH35 95% UTS Cond. 21  TCXHSH38 95% UTS Cond. 23  TCXQSH32 95% UTS Cond. 26.5  TCX26S32 50% UTS Cond. 27.4  TCX31H32 50% UTS Cond. 32  TCXCSH37 95% UTS Cond. 32  TCXUSH32 95% UTS Cond. 34	TCXLSH35 95% UTS Cond. 21 32  TCXHSH38 95% UTS Cond. 23 36  TCXQSH32 95% UTS Cond. 26.5 40  TCX26S32 50% UTS Cond. 27.4 40  TCX31H32 50% UTS Cond. 32 52  TCXCSH37 95% UTS Cond. 32 52  TCXUSH32 95% UTS Cond. 34 52	TCXLSH35 95% UTS Cond. 21 32 22  TCXHSH38 95% UTS Cond. 23 36 22  TCXQSH32 95% UTS Cond. 26.5 40 26  TCX26S32 50% UTS Cond. 27.4 40 26  TCX31H32 50% UTS Cond. 32 52 26  TCXCSH37 95% UTS Cond. 32 52 26  TCXUSH32 95% UTS Cond. 34 52 26	TCXLSH35 95% UTS Cond. 21 32 22 55  TCXHSH38 95% UTS Cond. 23 36 22 55  TCXQSH32 95% UTS Cond. 26.5 40 26 75  TCX26S32 50% UTS Cond. 27.4 40 26 75  TCX31H32 50% UTS Cond. 32 52 26 75  TCXCSH37 95% UTS Cond. 32 52 26 75  TCXUSH32 95% UTS Cond. 34 52 26 75	Catalogue: No         (kN)         BT         B2         B3         B4         B3           TCXLSH35         95% UTS Cond.         21         32         22         55         8.7           TCXHSH38         95% UTS Cond.         23         36         22         55         8.4           TCXQSH32         95% UTS Cond.         26.5         40         26         75         9.4           TCX26S32         50% UTS Cond.         27.4         40         26         75         —           TCX31H32         50% UTS Cond.         32         52         26         75         —           TCXCSH37         95% UTS Cond.         32         52         26         75         11           TCXUSH32         95% UTS Cond.         34         52         26         75         12.5	TCXLSH35 95% UTS Cond. 21 32 22 55 8.7 17  TCXHSH38 95% UTS Cond. 23 36 22 55 8.4 18  TCXQSH32 95% UTS Cond. 26.5 40 26 75 9.4 18.  TCX26S32 50% UTS Cond. 27.4 40 26 75 — —  TCX31H32 50% UTS Cond. 32 52 26 75 — —  TCXCSH37 95% UTS Cond. 32 52 26 75 11 22  TCXUSH32 95% UTS Cond. 34 52 26 75 12.5 24	Catalogue: No         (kN)         D2         D3         D4         D5         D7           TCXLSH35         95% UTS Cond         21         32         22         55         8.7         17         420           TCXQSH32         95% UTS Cond         23         36         22         55         8.4         18         480           TCXQSH32         95% UTS Cond         26.5         40         26         75         9.4         18         520           TCX31H32         50% UTS Cond         27.4         40         26         75         —         520           TCXCSH37         95% UTS Cond         32         52         26         75         11         22         650           TCXUSH32         95% UTS Cond         34         52         26         75         12.5         24         650



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	<b>D6</b>
<b>625 mm</b> <sup>2</sup>	ТСХ33Н38	50% UTS Cond.	34	52	24	16	35	620
<b>800 mm</b> <sup>2</sup>	ТСХ37Н33	50% UTS Cond.	38	59	24	16	35	620
1000 mm <sup>2</sup>	TCX41H31	50% UTS Cond.	43	60	24	16	35	620



All dimensions are in mm.


Website: www.yap-co.com







# Compression Dead end clamps for AAC & AAAC conductors



Wi	re	Catalogue.No	D Tl.	D1	D2	D3	D4	D5	D6
625	mm <sup>2</sup>	ТСХ33Н36	50% UTS Cond.	34	52	24	35	16	620
800	mm <sup>2</sup>	ТСХ37Н32	50% UTS Cond.	38	59	24	35	16	620
100	0 mm <sup>2</sup>	ТСХ41Н32	50% UTS Cond.	43	60	24	35	16	620




All dimensions are in mm.

Website: www.yap-co.com


E-mail: info@yap-co.com



# Compression Dead end Clamps for shield wire



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	D6
Core of Hawk	ТЅНН33	95% UTS Shield.	195	8.3	17	55	20	16
Core of Lynx	TSLH31	95% UTS Shield.	195	8.7	17	55	20	16
7 # 8	ТЅ78Н31	95% UTS Shield.	270	11	22	75	26	18
Core of Canary	TSCH31	95% UTS Shield.	270	11	22	75	26	18
Core of Curlew	TSUH31	95% UTS Shield.	270	11.5	22	75	26	18
Core of Martin	TSMH31	95% UTS Shield.	270	14	26	75	26	18
7 # 6	ТЅ76Н35	95% UTS Shield.	270	13.5	26	75	26	18
Ø11	TS111H31	95% UTS Shield.	270	12	22	75	26	18
80 mm <sup>2</sup>	TS80H31	95% UTS Shield.	270	12.5	24	75	26	18



For AW Wire

Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	D6	<b>D7</b>
7 # 8	ТЅ78Н33	95% UTS Shield.	270	11	32	75	26	18	178
7 # 6	ТЅ76Н31	95% UTS Shield.	270	13.5	38	75	26	18	178

Note:


All dimensions are in mm.

Website: www.yap-co.com


E-mail: info@yap-co.com



# Tension Clamp forConductor(Bolted type)








Catalogue.No Br. Load (kN)	D1		D3	D4	D5		
TB182403 95% UTS Cond.		18-24			12		
	33		16	275	14		





Catalogue.No	Br. Load (kN)	D1 D2	D3	D4	D5
TB182401		10.04	14	265	12



Note:

All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# **Earth wire Clamps & Grounding Systems**

# Parallel Grooves for Conductors Parallel Grooves and Tower Bondings for Shield wires Parallel Grooves and Tower Bondings for Grounding Systems Grounding Rods and Clamps 6/3 Grounding Wires 6/3


















Website: www.yap-co.com




# Parallel Grooves




Catalogue.No	D1	D2	Mat.
P1822S07	18-22	40	AL






Cata	logue.No	D1	D2	Mat.
P0′	718804	7-13	45	AL.
P0'	713801	7-13	45	St.





Catalogue.No	D1 D2 Mat.
P3237S01	32-37 57 AL





Tower Bonding

Catalogue.No	D1	D2	Mat
P1822S07	18-22	40	St.




Note:

All dimensions are in mm.

Website: www.yap-co.com




# Grounding System



$\underline{Connector}$			
Catalogue.No	D1	D2	Mat.
STUBCB01	29	20	Boronze

Also H.D.G Iron is available






Tower Bonding									
Catalogue.No	D1	D2	D3	Mat.					
G0713S05	13	35	7-13	Brass					

Also H.D.G Iron is available






Parallel G			
Catalogue.No	D1	D2	Mat.
P0713S06	7-13	30	Boronze

Also H.D.G Iron is available






Groundin	g R c	od		
Catalogue.No	D1	D2	Ma	t.
GRO15001	1500	16	Cu C	lad
GRO20003	2000	16	Cu C	lad
GRO20002	2000	20	Cu C	lad
GRO30003	3000	20	Cu C	lad

Also H.D.G Iron are available





Earthing Conductor					
Catalogue.No	D1	D2	Area	Mat.	
ECCU721	6.42	2.14	25	Cu	
ECCU725	7.56	2.52	35	Cu	
ECCU1917	8.9	1.78	50	Cu	

Note:

All dimensions are in mm.

Website: www.yap-co.com



# **Arcing Devices**

# TABLE OF CONTENTS


**PAGE** 

Arcing Horns	7/2 -7/3	
Arcing Rings	7/4	Tell Sin
Corona Rings	7/4	
	7/5	
	7/5 - 7/6	3
	7/6	
	7/7	
	7/7	


Website: www.yap-co.com




## Arcing Horns




Catalogue.No	Voltage (KV)	D1	D2	D3
NHUBS90	63-132	375	125	16
NHUBS0B	63-132	275	82	16
NHUBS0G	63-132	375	275	16




Catalogue.N	No Voltage D1	D2 D3
NHUBS01	63-132 275	170 16




Catalogue.No	Voltage (KV)	D1	D2	D3
NHUBSS40	63-132	375	125	16



	X 7 14			· ·
Catalogue.No	voitage	D1	D)	D2 :
	(KV)	$-\mathbf{D}\mathbf{I}$	U4	· D3 ·
NHI BS90	63-132		125	16
NIILDSSU		ر ا د		10



Catalogue.No	Voltage (KV)	D1	D2	D3
NHLBS01	63-132	275	82	16



Catalogue.No	Voltage (KV)	D1	D2	D3
NHLBS70	63-132	375	125	16



All dimensions are in mm.

All noted dimensions are upon Request.

Website: www.yap-co.com
















## Arcing Horns




Catalogue.No	Voltage (KV)	D1	D2	D3
NFUBS90	63-132	750	125	16






Catalogue.	No Voltage D1	D2 D3
NFUBS01	63-132 550	170 16




Catalogue.No	Voltage (KV)	D1	104	D3
NFUBS01J	63-132	550	170	16






NFLBS0A 63-132 550 82 16			
Catalogue.No         Voltage (KV)         D1         D2         D3           NFLBS0A         63-132         550         82         16			
NFLBS0A 63-132 550 82 16	Cotologue No Voltage		
NFLBS0A 63-132 550 82 16		DI DZ DS	
NFLBS0A 63-132 550 82 16			
NFLBS0A 63-132 550 82 16			
NFLBS0A 63-132 550 82 16			
11220011	NEL RS0A 63-132	550 82 16	
			_





Catalogue.No	Voltage (KV)	D1	D2 D3
NFLBS01	63-132	550	82 16





Catalogue.No	Voltage D1	D2	D3
NFLBSS08	63-132 550	200	16




### Notes:


All dimensions are in mm.
All noted dimensions are upon Request.

Website: www.yap-co.com



## Arcing Rings






Catalogue.No	Voltage (KV)	D1	D2	D3	D4	D5
NRHDS02T	63-132	282	100	90	20	16










	logue.No Vo	oltage (KV) D1	D2 D3
NR	HDS0B 6		200 16












Catalogue.No	Voltage (KV)	D1	D2	D3
NHLRCS0B	230	300	250	20



All dimensions are in mm.


 $All\ noted\ dimensions\ are\ upon\ Request.$ 



E-mail: info@yap-co.com




## Corona Rings




Catalogue.No	Voltage (KV)	D1	D2	D3	D4
NRHDS01	400	695	540	295	50






Catalogue.No	Voltage (KV)	D1	D2	D3	D4
NFLRN015		1080	1080	336	50



Catalogue.No	(KV)	D1	D2	D3	D4
NFLRN015		1080	1080	336	50



Catalogue.No	Voltage (KV)	D1 D2	D3	D4
NFLRAS0B	400	500 850	300	50



### Notes:

All dimensions are in mm.


All Noted dimensions are upon Request.

Website: www.yap-co.com

E-mail: info@yap-co.com




## Corona Ring




Catalogue.No	Voltage (KV)	D1	D2	D3	D4	D5
NFLRAS01	400	1030	700	350	260	50





Catalogue.No	Voltage (KV)	D1	D2	D3
NRHDS0E	400	385	138	62





	*****				
Catalogue.No	Voltage (KV)	D1	D2	D3	
NRHDSS0H	400	1250	322	50	



### Notes:


All dimensions are in mm.
All noted dimensions are upon Request.

Website: www.yap-co.com

E-mail: info@yap-co.com




## Corona Rings




Catalogue.No	Voltage (KV)	D1	D2	D3
NRHDS01B	230-400	350	104	38






Catalogue.No	Voltage (KV)	D1	D2	D3
NRHDS01P	230-400	350	271	40





Catalogue.No	(KV)	D2 D3
NRHDS01L	230-400 260	283 34





Catalogue.No	Voltage (KV)	D1	D2	D3
NRHDSS02	400	600	90	50

### Notes:

All dimensions are in mm.
All noted dimensions are upon

All noted dimensions are upon Request.

Website: www.yap-co.com



## Spacers & Spacer Dampers

### TABLE OF CONTENTS

**PAGE** 

8/3

Spacers 8/2

Single Hinge Spacer Dampers


Double Hinges Spacer Dampers 8/4



Website: www.yap-co.com




### **Spacers**



Wire	Catalogue.No	D1	D2
Squab	SP222601	457	22-26
Curlew	SP283201	457	28-32





Wire	Catalogue.No	D1	D2
Lynx-Hawk	SPS19301	457	19-22
Squab	SPS22401	457	22-26
Canary	SPC28401	457	28-32



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com




## Spacer Dampers




Catalogue.No	D1	D2
KPCH2102	330	21.5-24.7





Catalogue.No	D1	D2
KPCS2840	457	21.5-24.7
KPCU2840	457	28-32





Catalogue.No	D1	D2
K3SS1LW0	457	21.5-24.7
K3SU1LW0	330	28-32



Note:


All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com




## Spacer Dampers



Catalogue.No	D1	D2
K2SS2LS1	457	24.5
K2SU2LS1	457	31.6





Catalogue.No	D1	D2
K3SS2LW2	457	24.5
K3SU2LW2	457	31.6



Note:

All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



# **Stock Bridge Dampers**

### TABLE OF CONTENTS

**PAGE** 

Stock Bridge Dampers for Conductors

9/2



Stock Bridge Dampers for Shield wires


9/2



Website: www.yap-co.com




## Stock Bridge Dampers




Catalogue.No	D1	D2
KCC28401	512	28-32





Catalogue.No	D1	D2
KCL19002	422	19-29





Catalogue.No	D1	D2
KS708122	330	8-12
KS142201	330	14-22



Note:

All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com



## Accessories

### TABLE OF CONTENTS

**PAGE** 

Midspan Joints

10/2 - 10/3

Repair Sleeves

10/4

Warning Balls

10/5

Counter Weights


10/5



Website: www.yap-co.com



## Midspan Joints For Conductor



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3	D4	D5	D6
Hyena	MCXYS32	95% UTS Cond.	550	15.5	25	200	6.5	12
Linnet	MCXIS3	95% UTS Cond.	440	19.5	30	200	7.1	16
Lynx	MCXLS37	95% UTS Cond.	440	21	32	200	8.7	17
Hawk	MCXHS34	95% UTS Cond.	660	23	36	230	8.4	18
Squab	MCXSS3	95% UTS Cond.	700	26.5	40	230	9.4	18
Drake	MCXDS3	95% UTS Cond.	900	32	52	230	11	22
Canary	MCXCS3	95% UTS Cond.	900	32	52	230	11	22
Rail	MCXRAS3	95% UTS Cond.	900	32	52	230	8 .	17
Curlew	MCXUS32	95% UTS Cond.	900	34	52	230	11.5	22




Note:

All dimensions are in mm.


Website: www.yap-co.com



## Midspan Joints For Shield Wire



Wire	Catalogue.No	Br. Load(kN)	D1	D2	D3
3 NO 6	MS362331	95% UTS Shield	230	9.4	22
Core of Hawk	MSHS2331	95% UTS Shield	230	8.4	18
Core of Squab	MSSDS233	95% UTS Shield	230	9.4	18
Core of Lynx	MSLDS203	95% UTS Shield	200	8.7	17
7 NO 8	MS7DS233	95% UTS Shield	230	11	22
Core of Canary	MSCDS233	95% UTS Shield	230	11	22
Core of Curlew	MSUDS263	95% UTS Shield	260	11.5	22
Core of Curlew	MSUDS233	95% UTS Shield	230	11.5	22



Mid Span for AW Wires

	Catalogue.No		D1	D2	D3	D4	D5	D6
7 No 8		95% UTS Shield	230	23	32	230	11	22
7 No 6	MISOSSI	JUTO CID DINOIG		28			13.5	26


### Note:

All dimensions are in mm.

Website: www.yap-co.com



## Repair Sleeves



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3
Lynx	RCLA2031	95% UTS Cond.	200	21	
Curlew	TTC C11000	95% UTS Cond.	300	34	52



Wire	Catalogue.No	Br. Load (kN)	D1	D2	D3
Hyena	RCYA2003	95% UTS Cond.	200	15.5	25
Linnet	RCIA2003	95% UTS Cond.	200	19.5	30
Orioal	RCLA2003	95% UTS Cond.	200	21	36
Lynx	RCLA2203	95% UTS Cond.	220	21	32
Hawk	RCHA2503	95% UTS Cond.	250	23	36
Squab	RCSA3003	95% UTS Cond.	300	26.5	40
Drake	RCDA3003	95% UTS Cond.	300	30	50
Canary	RCCA3003	95% UTS Cond.	300	32	52
Rail	RCRAA303	95% UTS Cond.	300	32	52




All dimensions are in mm.

Website: www.yap-co.com






### Accessories



Weight

Catalogue.No	D1	Weight
I02H01	19-22	2.5






			ļ	Ì	1	2		ć		?	i	į	,	٤	)	l		Į	l	ţ	
	_	ı			ı				,			į	•	-	•	ı					
	1		ì	•			•		ì	•		ì				ï	,	٦	ï	ī	

Catalogue.No	D1	D2	No. of Weight	Weight
125CS04	276	265	1	25.3
125HS03	276	265	2	48.8
125HS05	351	265	3	72.5
125CS05	426	265	4	96.4
I25HS07	501	265	5	119.9





Warning Ball

Catalogue.No	D1	D2
WBS08131	600	8-13
WBC12181	600	12-18
WBC18221	600	18-22
WBC22271	600	22-27



Note:

All dimensions are in mm.

Website: www.yap-co.com




# **OPGW Fittings**

TABLE OF CONTENTS	PAGE
Suspension Clamps	11/2
Dead end grips	11/3
Protection Rods	11/3
Parallel Grooves	11/4
Fastening Clamps	11/4
Earthing Bonds	11/5
Thimble clevises	11/6
Stockbrdige Dampers	11/7
Warning Balls	11/7
Armorrods	11/8 - 11/9
Joint Boxes	11/10

Website: www.yap-co.com




### OPGW Accessories



Catalogue.No Br. Load (kN)	D1 D2
SSAHOS02 70	56 20





Wire	Catalogue.No	D1
10.05	OPGWRU14	175
10.2	OPGWRU14	175
10.5	OPGWRU14	175
12	OPGWRU26	175
12.7	OPGWRU12	175
13.5	OPGWRU12	175
15	OPGWRU21	175




### Notes:

All dimensions are in mm. Rubbers for all other diameters between  $\emptyset$  10 to  $\emptyset$  17.5 are available.

Website: www.yap-co.com



## **OPGW Tension Clamps**



### Protection Rod

Wire	Catalogue.No	D1	D2	No. of Rod/Set	
10.05	TGOPS018	2030	2.64	12	
10.2	TGOPS018	2030	2.64	13	
10.5	TGOPS016	2080	2.64	13	
12	TGOPS013	2170	2.64	14	
12.7	TGOPS019A	2190	2.64	16	
13.5	TGOPS019	2500	3.4	13	
15	TGOPS03	2380	2.9	15	

Dead End Grip

2000				
Wire	Catalogue.No	D3	D4	No. of Rod/Set
10.05	TGOPS018	1500	3.25	7
10.2	TGOPS018	1500	3.25	7
10.5	TGOPS016	1500	3.25	7
12	TGOPS013	1520	3.25	8
12.7	TGOPS019A	1550	3.25	8
13.5	TGOPS019	1470	4.65	6
15	TGOPS03	1800	4.65	6



All dimensions are in mm.


Tension Clamps for all other diameters between  $\emptyset$  10 to  $\emptyset$  17.5 are available.

Website: www.yap-co.com

E-mail: info@yap-co.com




### **OPGW** Accessories



### Parallel Groove

Wire	Catalogue.No	D1	D2	D3
10.05	P1000A02	10.5	10.5	40
10.2	P1000A02	10.5	10.5	40
10.5	P1000A02	10.5	10.5	40
12	P1200A02	12	15	40
12.7	P1200A02	12.7	15	40
13.5	P1315S01	13.5	15	40
15	P1515S01	15	15	40





Fastening Clamp

Wire	Catalogue.No	D1	D2	D3
10.05	F10G2500	10.5	45	12
10.2	F10G2500	10.5	45	12
10.5	F10G2500	10.5	45	12
12	F12G2500	12	45	12
12.7	F12G2500	12	45	12
13.5	F13G2500	13.5	45	12
15	F15G2500	15	45	12



### Notes:

All dimensions are in mm.


Accessories for all other diameters between  $\emptyset$  10 to  $\emptyset$  17.5 are available.


Website: www.yap-co.com


E-mail: info@yap-co.com




### Earthing Bonds









#### Notes:

D2

All dimensions are in mm.

Material of Wires and Clamps are Aluminium.


Earthing Bonds for all other diameters between Ø 10 to Ø 17.5 are available.

Website: www.yap-co.com

E-mail: info@yap-co.com




### **OPGW** Accessories




#### Extension Link

Catalogue.No	Br. Load (kN)	D1
LE030010	70	300







Wire	Catalogue.No	Br. Load (kN)	D1	D3	Material
10.05	TC132522	120	55	21	Ductile Iron
10.2	TC132522	120	55	21	Ductile Iron
10.5	TC132522	120	55	21	Ductile Iron
12	TC132522	120	55	21	Ductile Iron
12.7	TC132522	120	55	21	Ductile Iron
13.5	TC493801	120	79	22	Ductile Iron
15	TC493801	120	79	22	Ductile Iron



### Notes:

All dimensions are in mm.


Thimble Clevises for all other diameters between  $\emptyset$  10 to  $\emptyset$  17.5 are available.

Website: www.yap-co.com

E-mail: info@yap-co.com




### **OPGW** Accessories




Warning Ball						
Catalogue.No	D1	D2				
WBC12181	600	12-18				
WBC18221	600	18-22				
WBC22271	600	22-27				





	Damper	
Wire	Catalogue.No	D1 D2
10-13.5	KS142201	330 14-22





Damper					
Wire	Catalogue.No	D1	D2		
13.5-17.5	KCL19002	422	19-29		




### Note:

All dimensions are in mm.

Website: www.yap-co.com



## Armour Rods (OPGW)



For Suspension Clamp

Wire	Catalogue.No	D1	D2	No. of Rod/Set
10.05	AO1037S1	1800	3.7	10
10.2	AO0942S1	1800	4.24	9
10.5	AO0942S1	1800	4.24	9
12	AO01004L	1800	4.24	10
12.7	ASO110AL	1800	4.24	11
13.5	ASO1242S	1800	4.24	12
15	ASO1105L	1800	4.6	11



All dimensions are in mm.

Armor Rods for all other diameters between  $\emptyset$  10 to  $\emptyset$  17.5 are available.


Website: www.yap-co.com

E-mail: info@yap-co.com



**-** 11/8 ·

## Armour Rods(OPGW)



### For Damper

***************************************						
No. of Rod/Set						
10						
10						
11						
10						
11						
11						
11						

### For Warning Ball

Wire	Catalogue.No	D1	D2	No. of Rod/Set
10.05	ASO1037W	1000	3.7	10
10.2	ASO1037W	1000	3.7	10
10.5	ASO1137W	1000	3.7	11
12	ASO1004W	1000	4.24	10
12.7	ASO1104W	1000	4.24	11
13.5	ASO1142W	1000	4.24	11
15	ASO1104S	1000	4.6	11



All dimensions are in mm.


Armor Rods for all other diameters between Ø 10 to Ø 17.5 are available.

Website: www.yap-co.com

E-mail: info@yap-co.com



### Joint Boxes



D1

 $\Box$ 

### 2 way Joint box


Catalogue.No	D1	D2	D3
OPGWJB01	302	152	10-17.5





Catalogue.No	D1	D2	D3
OPGWJB03	323	200	10-17.5









Catalogue.No	D1	D2	D3
ОРТСЈВ11	10	10	12



Note:

All dimensions are in mm.

Website: www.yap-co.com

E-mail: info@yap-co.com

